

## **Horizontal machining center (JN-H50)**

# Technical Document

By Jiangnan CNC Machine Co., Ltd.

By Jiangnan Technology (Songyang) Co., Ltd.



The picture is for reference only, the actual appearance may vary slightly due to selected configurations.

Party A: :

Party B: Jiangnan CNC Machine Tool Co., Ltd.

Date:

Date:

## 1. Company Profile



Jiangnan CNC Machine Tool Co., Ltd. is located in the beautiful coastal city of Wenzhou, China. It is a CNC machine manufacturing enterprise integrating research, design, manufacturing, and sales. The company was established in September 2006 and currently has a standardized plant covering an area of 85,000 square meters, with more than 180 excellent staff members. Among them, 90 employees have a college degree or above, accounting for 50% of the total staff; the company has 20 research and development personnel, accounting for 9% of the total workforce.

Adhering to the business philosophy of "technological innovation, win-win cooperation, integrity and efficiency, sincere service," and the quality policy of "quality first, customer foremost," the company provides customers with the most cost-effective products and comprehensive services, aiming to create the maximum value for customers. With advanced equipment including the world's most advanced large-scale CNC five-axis machining center and horizontal machining center, as well as contour grinding machines and high-precision Renishaw inspection equipment, the company strictly adheres to international standards. It has obtained ISO9001 certification and implements rigorous process inspections to ensure product quality.

The company mainly manufactures vertical Machining Centers, horizontal Machining Centers, drilling and tapping machine, gantry series, CNC lathes, and other series of products:

1. Vertical Machining Centers: JN-IV850, JN-NV856, JN-NV900, JN-NV1050, JN-IV1160, JN-NV1300, JN-NV1690, etc.
2. Horizontal Machining Centers: JN-H50, JN-IH50, JN-H63, JN-IH63, JN-H800, JN-H1810, etc.
3. Drilling and Tapping Machines: JN-T500, JN-T700, etc.
4. CNC Lathes: JN-CH106, JN-CH108, JN-CH108M, JN-CH108MY, JN-CH208, JN-CH506MSY, etc.
5. Gantry Series: JN-GL2013, JN-GL2015, JN-GL2518, JN-GL2720, JN-GL3023, JN-GL4023, JN-GL4027, JN-GL5030C, etc.

Our machine tools are popular in major provinces and cities in China, including Beijing, Shanghai, Chongqing, Tianjin, Hebei, Henan, Shanxi, Shandong, Jiangsu, Zhejiang, Guangdong, Anhui, Hubei, Fujian, and others, due to their excellent performance and first-class after-sales service. The company adopts a combination of direct sales and distributorship models and has cooperated with 100 distributors nationwide, covering major cities across the country.

Jiangnan CNC – A national brand, a national pride! We sincerely invite you to join with us to create a new era of high-tech machinery!

## 2.Introduction the Songyang Factory



Jiangnan Technology (Songyang) Co., Ltd., a wholly-owned subsidiary of Jiangnan CNC

Machine Tool Co., Ltd., was established in August 2017. Located in the beautiful scenic city of Songyang, Lishui, it covers an area of 107.69 acres with a total construction area of 29,693 square meters. The company has a registered capital of 50 million yuan, with fixed asset investment of 300 million yuan and working capital investment of 70 million yuan. It has introduced multiple sets of high-precision equipment such as the Japanese DAIWA CNC gantry five-axis machining center and horizontal machining centers.

Building on the development foundation of its parent company, Jiangnan Technology actively promotes brand building and product serialization strategies. Internally, it implements ERP systems and information construction, optimizing business processes, and enhancing the company's management level and core competitiveness. Facing the challenges of economic globalization, Jiangnan will continue to focus on the CNC machining center industry, adhere to market-oriented business philosophy, and persist in the direction of "internationalization, technologicalization, and industrialization." It will vigorously introduce advanced equipment, technology, and talents, integrate resources, leverage strengths, and strive to shape "Jiangnan" into a well-known enterprise in the international CNC machining center industry.

### 3.The technical parameters of the JN-H50

Item		Unit	Specification
Worktable	Table size	mm	500*500
	Indexing angle	°	1°(optional 0.001°, 5°)
	Max. swing diameter	mm	1250
	Table load	kg	500
Travel	X/Y/Z axis travel	mm	800/600/650
	Spindle nose to table center	mm	150-800
	Spindle center to table surface	mm	80-680
Worktable	Spindle diameter		Φ190
	Spindle speed	rpm	6000
	Spindle drive method		Belt-type
Travel	Spindle motor	kw	15-18.5
Worktable	X/Y/Z cutting feed	mm/min	1 ~ 10000
	X/Y/Z rapid feed	m/min	20/20/20
Travel	Positioning accuracy	mm	0.008
	Repeat positioning accuracy	mm	0.005

	Indexing accuracy (1°/5°)	sec	8
	Repetition accuracy (1°/5°)	sec	2
	Indexing accuracy (0.001°)	sec	15
	Repetition accuracy (0.001°)	sec	6
Automatic Tool Change System (Optional)	Tool magazine capacity	T	24
	Tool change mode		
	Max. tool diameter	mm	Φ110
	Max. tool diameter(Adjacent vacant)	mm	φ200
	Max. tool length	mm	400
	Max. tool weight	kg	15
	Toolholder type		BT50
	Tool change time	s	8 (T-T)
Others	Air pressure demand	kg/cm2	5-7
	Cooling pump	w	1270
	Power requirement	KVA	50
	Machine weight	kg	10000
	Machine size	mm	3800*5000*3000

The actual values for power supply, air pressure source, machine weight, and overall dimensions may vary due to different configurations and peripheral equipment.

#### 4.Detailed supplier of main components

NO.	Name	Manufacturer	Brand Origin	Remarks
1	CNC System	SIMENS	Germany	
2	Spindle Motor	SIMENS	Germany	
3	X/Y/Z Axis	SIMENS	Germany	
4	Ballscrew (X/Y/Z Axis)	PMI/ HIWIN	Taiwan	50/50/50
5	Linear Guideway (X/Y/Z Axis)	PMI/ HIWIN	Taiwan	X45 /Y45/ Z55
6	Ballscrew Coupling	JANETECH	Taiwan	
7	Bearing	NACHI	Japan	
8	Electric Lubrication System	HERG	Joint Venture	
9	Spindle	POSA	Taiwan	
10	Tool Magazine	CHNCIT/OKADA	China	

11	Cooling Pump	STAIRS	Taiwan	
12	Pneumatic Components	SMC	Japan	
13	Transformer	LUHO		
14	Electrical Components	Schneider	France	
15	Telescopic Cover	CHNCIT/ETEK	Taiwan	
16	Screw + chain plate chip conveyor	CHNCIT		
17	Machine tool peripheral sheet metal	CHNCIT		
18	fourth axis	DETRON	Taiwan	500*500
19	hydraulic station	7OCEAN	Taiwan	

Note: If any supplier fails to supply, it will be replaced with a brand of equal quality without further notice.

### 5.Optional accessories list

No.	Name	Quantity/Unit	Note
1			
2			
3			
4			
5			
6			
7			
8			

### 6.Tools and manuals list

No.	Name	Quantity/Unit	Remarks
1	Toolbox	1Set	
2	Certificate of conformity	1Copy	
3	Machine specification	1Set	
4	System specification	1Set	
5	Air gun	1 Piece	

---

## 7. Machine Mechanical Indicators

### 1、 Machine Structure

Machine Structure The main structural components of the machine tool are made of high-tensile cast iron, optimized in design for high static rigidity. The spindle features a high-rigidity structure, high mechanical efficiency, suitable for high-precision heavy cutting machining. The spindle motor adopts AC servo technology, enabling stepless speed regulation in both forward and reverse directions. The three-axis ball screw and servo motor drive directly, with no transmission cumulative error, ensuring high repeatability and positioning accuracy. Automatic tool changing structure, quick and smooth tool changing operation. All machine components and various measurement units comply with international (ISO) standards.

### 2、 Machine Protection

Machine Protection The machine protection device is safe, complete, and reliable. Machine noise: in compliance with national standards, 75dB. Electrical control cabinet sealed to prevent dust and water, IP65 rating.

### 3、 Lubrication System

Lubrication System Adopts TZ electric lubrication device to quantitatively lubricate all sliding surfaces and ball screws. Adjustable lubrication time intervals and amounts to ensure 100% lubrication at all lubrication points. Machine displays an alarm in case of low oil level (oil shortage). Uses 68# guide rail lubricating oil. Lubrication tank capacity: 2 liters. Lubrication pump voltage: 220V, motor output power: 25W, maximum pressure: 2.5MPa, discharge flow rate: 110ml/min.

### 4、 Pneumatic System

Pneumatic System Pneumatic system, pressure switches, solenoid valves, etc., realize pneumatic tool changing, pressure: 6-8KG/C m<sup>2</sup>, flow rate: 220L/MIN, can clean the working area.

### 5、 Electrical System

Electrical System The standard system has complete and reliable interlocking, safety protection, and fault self-diagnosis alarm functions. Equipped with RS232 standard communication interface, can use computer floppy disk for program storage. (Other systems can be provided according to user requirements).